

## Toleranztabelle Rohre

Längentoleranz +0/+3%

Außendurchmesser [mm]	Toleranz Außendurchmesser [mm]		Toleranz Innendurchmesser [mm]	
50 - 115	+ 1,0	+ 5,0	- 2,0	- 5,0
120 - 150	+ 2,0	+ 7,0	- 2,0	- 7,0
160 - 180	+ 2,0	+ 8,0	- 2,0	- 8,0
190 - 220	+ 2,0	+ 9,0	- 2,0	- 9,0
230 - 250	+ 3,0	+ 10,0	- 3,0	- 10,0
260 - 300	+ 3,0	+ 12,0	- 3,0	- 12,0
310 - 400	+ 3,0	+ 14,0	- 3,0	- 14,0
410 - 500	+ 3,0	+ 16,0	- 3,0	- 16,0
505 - 750	+ 5,0	+ 20,0	- 5,0	- 20,0
750 - 1000	+ 5,0	+ 25,0	- 5,0	- 25,0
1000 - 1250	+ 6,0	+ 30,0	- 6,0	- 30,0
1250 - 1500	+ 6,0	+ 40,0	- 6,0	- 40,0
1500 - 2000	+ 10,0	+ 50,0	- 10,0	- 50,0
> 2000	+ 15,0	+ 60,0	- 15,0	- 60,0